

www.seattledoorandmillwork.com 206.450.9560

Interior Rough Openings



R.O. Width

Jambs: 1 7/16" Gaps: 3/16" Shim Space: 1/2" Doors + 2 1/8""= R.O.

Inswing: Door + 2 7/8" Outswing: Door + 1 9/16"

Double Door Unit with Astragal



R.O. Width

Mull Post: 1 1/8" Gaps: 1/4" Shim Space: 1/2" Doors + Sidelight +3 5/16"= R.O.

R.O. Width

Inswing: Door + 2 7/8" Outswing: Door + 1 9/16"

Double Door Unit without Astragal



R.O. Width Mull Post: 2 1/4" Gaps: 5/16" Shim Space: 1/2"

Doors + Sidelights + 4 1/2"= R.O.

R.O. Width

Inswing: Door + 2 7/8" Outswing: Door + 1 9/16"

Interior Finished Openings



Finished Width

Door Panels + 1/2" = F.O.

Finished Height

79" Doors + 1 3/4" = F.O.

Double Bifold Door (with manufacturer's hardware)



Finished Width

Doors Panels + 1" = F.O.

Finished Height

79" Doors + 1 3/4" = F.O.

Single Bipass Door (with manufacturer's hardware)



Finished Width

Door width x 2 - 1 3/4" = F.O.

Finished Height

Door + 1 3/4" = F.O. (No carpet)