



2448 Spinner Hanger



GOFF®

“Blasting Solutions”

Features

Pitless Design

Continuous Production

(2) 5 HP Direct Drive Blast Wheel

Single 14 Inch Lip Separator

Abrasive Resistant Blast Chambers

Multiple Indexing

Safety Interlocks

500 Lb. Hook Capacity

SPECIFICATIONS—2448

EQUIPMENT DIMENSIONS

| | 2448 | 1016DC |
|---------------|-----------|----------|
| Width | 6' | 62" |
| Height | 11'9-1/4" | 117-3/4" |
| Length | 8'3-5/8" | 62" |
| Weight | 3,500 | 900 |

AIRLESS BLAST UNITS

WHEEL: Two direct drive blast wheel revolves at 3600 RPM for maximum abrasive velocity. 9" diameter wheel with 4 curved blades 2" wide is standard. Balanced wheel components assure smooth operation.

BLADES: Unique snap lock design eases blade replacement. Cast from abrasive resistant alloy to insure maximum life. Curved blade design provides maximum abrasive control.

WHEEL HOUSING: Fabricated from 1/4" steel plate. Housing lined with cast interlocking abrasive resistant liners.

CONTROL CAGE: Dial type enclosed cage gives positive adjustment of blast pattern. Cast alloy steel construction.

CABINET CONSTRUCTION

CABINET: Pitless type, all welded structurally reinforced cabinet fabricated from 1/4" steel plate. Rear door provides access to blast chamber for periodic inspection and maintenance of blast wheels

BLAST CHAMBER CONSTRUCTION

DUAL CHAMBER: Chambers are constructed with manganese sidewalls and backwalls with abrasive resistant lined roof and bottom cast lined chamber is optional. Hook spindles are provided in each chamber.

SEALS: Dual heavy-duty rubber seals on chamber sides and top. Abrasive accumulation on chamber bottom provides positive sealing of blast chamber during operation. Unique seal design reduces any abrasive leakage.

CHAMBER SPEED: 3 RPM

DRIVE: Exterior mounted electric motor and gear reducer transmit power through a chain driven wheel to revolve chamber. Adjustable stops on chamber top working in conjunction

Goff, Inc.
12216 NS352
PO Box 1607
Seminole, Oklahoma 74818-1607
USA

Tel 405-382-6900
Tel 800-654-4633
Fax 405-382-7013

www.goff-inc.com
goff@goff-inc.com

with automatic electrical switching provide variable indexing. Number of index stops variable from one to three per chamber.

HOOK SPINDLE: Continual rotation of hook spindle during blasting operation provides full exposure of parts to the blast pattern. 15 RPM., Capacity 500 pounds maximum.

CAPACITY: Maximum area provided for material to be blasted is 24" diameter x 36" long.

ABRASIVE RECYCLING SYSTEM

ELEVATOR: Centrifugal discharge belt and bucket elevator is rigid and dust tight. Removable doors permit service and inspection. All shaft bearings are exterior mounted for extended life. Screw adjusted take-up provides positive belt adjustment.

SCREENING: Primary screen in cabinet protects screw conveyor and elevator from large objects. A perforated screen above hopper removes small foreign objects from abrasive.

CABINET VENTILATION: Air inlet and outlet positioned to provide maximum dust evacuation of blasting zone.

ABRASIVE REQUIRED: 350 pounds.

ABRASIVE CONTROL: Fully adjustable butterfly valve provides precise flow control of abrasive. Totally enclosed design means maximum noise suppression.

SEPARATOR: 14" gravity lip separator has adjustable abrasive spreader and refuse gate for maximum contaminate removal.

VENTILATION FEATURES

Optional 1,160 CFM Dust Collector is self contained and is an optional feature. Collector contains (10) 8" diameter by 16" long cartridges which are cleaned automatically by an air pulse unit (requires 80 to 110 PSI of air 2 CFM). Free standing collector accommodate 55 gallon refuse drum.

ELECTRICS

NEMA type 12 electrical enclosure, fusible disconnect switch, thermal overload protection on all motors, 230/460 volt primary, 115 secondary control transformer, blast wheel ammeters, oil tight push buttons, hour meter, automatic reset abrasive cycle timer. Chamber lockout and independent blast wheel operation for precise blast pattern test.

SAFETY FEATURES

Blast wheels operational only when rear door is securely closed. Double positive contact chamber seals prevent stray abrasive. Abrasive valves operative only during timed blast cycle. Emergency stop button provided on control panel.

NOISE LEVEL: Approx. 85 DB.

Specifications subject to change without notice..

GOFF®

"Blasting Solutions"