

Ph# 850-762-3221

On top you will see a **bolt** sticking up. This bolt is on a **swivel**. If you want to lock the latch in the open position while pulling tractor away from implement, you would simply lift the lever and slide the bolt under the lever. This will hold the latch open

1 Raise lever up and slide **bolt** underneath the lever with finger tips. This will hold latch open while pulling tractor away from the implement

2 This is a lever that will allow you to manually open the latch. As you lift the lever with your finger tips you will steel spring that operates the latch. You place fingers here and lift

3 A U Bolt fits over and around the drag arm and slips through the bolt holes as shown on the bottom and back of the quick connect. Once the U Bolt is tighten up this will keep the quick connect straight and level with the drag arm

4 Each end of the stabilizer bar has a 90 degree hook. To use the stabilizer bar you would hook each end into the **hole** on the end of the pin that holds the Quick Connects onto the drag arm of the 3 point hitch.

5 The stabilizer bar is in two pieces. One piece slides inside the other in order to adjust the distance between the two drag arms of the three point hitch. Once you get the distance set there is a knob with a hand grip that you can turn in order to tighten down the stabilizer bar to prevent any slippage in the adjustment.

6. You can hook a category 2 quick connect to a implement with a category 1 hook up, but you would need to slip a bushing over the category pin on the implement to use as a spacer. The bushing can be found at Tractor Supply Stores or Tractor Dealer Stores.

7 The same would be for the Category 3 quick connect for implements with a Category 1 or 2 hook up.

We also have:

Model 112- Category 1 quick connect with a category 2 hook \$ 209.00

Model 221 - Category 2 quick connect with a category 1 hook \$ 209.00

Model 223 - Category 2 quick connect with a category 3 hook \$ 265.00

Model 332 - Category 3 quick connect with a category 2 hook \$ 265.00

Stabilizer Bar \$ 20.00

Shipping is \$ 20.00 for each category with the stabilizer bar.

Weld on units

Model W102 cat #1 \$ 145.00

Model W202 cat # 2 155.00

Model W303 cat # 3 245.00

8 The Stabilizer cannot be used when using a PTO driven implement. The stabilizer would be in the way of the PTO shaft.

9 Not often, but on some tractor models the top center link of the three point hitch can be too short after installing the quick connects. We have top links that we can provide at our cost for **\$ 30.00** .

Note: the quick connects will add 3 1/2" to the length of the drag arms of your three point hitch.

10 One way of determining your three point hitch category size is by measuring the pin hole on the drag arms.

Category 1 hitch PIN HOLE SIZE IS 7/8"

Category 2 hitch PIN HOLE SIZE IS 1 1/8"

Category 3 hitch PIN HOLE SIZE IS 17/16"

11 Lynch Pins are used to keep the pins from sliding out of the quick connect hook.

For more information or to order place shipping address in the comment box below. You can also call 850-762-3221.

