

MATERIAL SAFETY DATA SHEET

HAZARD RATINGS
Health: 2
Flammability: 2
Reactivity: 0
Personal Protection: B

NOTICE: Judgment may be based on indirect test and technical literature. The OSHA Hazard Communication Standard only requires MSDS's and special labeling for materials defined as "HAZARDOUS"; see 29 CFR 1910.1200 (c). This document may be about a product which is NOT hazardous but is provided as information for our customers. See references for information.

SECTION I.

PRODUCT IDENTIFICATION

Product Identifier: Traffic Lane Conditioner
Product VOC: 8%
Manufactured by: Kor-Chem, Inc.
Manufactured for: Polymer Concepts, Inc.
705 Hembree Place, Suite A
Roswell, GA 30076
Phone: 678-802-6018

Product Identification #(PIF): 2774
Emergency Telephone #: 1-800-255-3924
General Information #: 404-344-9580
Prepared by: Sonya Lockhart
Date Prepared: February 1, 2005

SECTION II.

HAZARDOUS INGREDIENTS

	CAS #	OSHA/PEL	TLV	STEL	max. %
1. Propylene glycol monomethyl ether	107-98-2	100 ppm	100 ppm	150 ppm	7
2. Propylene Glycol	57-55-6	NE	NE	NE	3

SECTION III.

HEALTH HAZARD INFORMATION

.....Primary Routes of Entry: X Skin X Eyes Inhalation Ingestion

♦ *Effects of overexposure:*

- Eye Contact: Liquid may cause mild eye irritation with redness, pain and tearing.
- Skin Contact: Causes defatting of the skin which can lead to irritation and dermatitis.
- Inhalation: Vapors or mists in large amounts may cause irritation to nose, throat, and respiratory tract. High vapor concentrations may result in CNS depression.
- Ingestion: Swallowing large amounts may be harmful.

SECTION IV.

EMERGENCY FIRST AID

- ♦ *Eyes:* Flush well with water for at least 15 minutes. Seek medical attention if irritation persists.
- ♦ *Skin:* Wash with soap and water. Seek medical attention if irritation persists.
- ♦ *Inhalation:* Move to fresh air.
- ♦ *Ingestion:* Drink lots of water to dilute, **DO NOT INDUCE VOMITING.** Get medical help.

SECTION V.

FIRE & EXPLOSION DATA

Flammability: COMBUSTIBLE
Means of extinction: Water spray, dry chemicals, CO₂.
Autoignition Temperature: ND
Hazardous combustion products: Carbon monoxide, carbon dioxide.
♦ *Special Fire Fighting Procedures:* Wear self-contained breathing apparatus; avoid breathing vapor (fumes) of heated product.
♦ *Unusual Fire Fighting Hazard:* NONE.

Flash Point: 150° F
Upper Flammability Limit (% by volume): ND
Lower Flammability Limit (% by volume): ND

SECTION VI.

REACTIVITY DATA

Chemical stability: Stable
Hazardous polymerization: Will not occur.
Incompatibility with other substances: Strong oxidizing agents, strong acids and strong bases.
Reactivity, and under what conditions? NONE.
Hazardous decomposition products: Carbon dioxide, and carbon monoxide.

SECTION VII.

HANDLING & STORAGE

Storage: Keep container closed, when not in use. Keep away from heat, flame, or sunlight. Protect from physical damage.
Handling: Do not premix with other chemicals. Exercise reasonable care and precaution. Keep out of reach of children.

SECTION VIII.

EXPOSURE CONTROL/PERSONAL PROTECTION

Personal protective equipment: Use rubber gloves and eye protection.

Gloves (specify): Chemical resistant gloves

Eye (specify): Chemical resistant eye ware

Clothing (specify): Normal materials handling clothing.

Respirator (specify): NA

Footwear (specify): Chemical resistant shoes

Other: NONE

SECTION IX.

SPECIAL PRECAUTIONS/ OTHER COMMENTS

Carefully read all instructions on label before handling this product. "FOR INDUSTRIAL USE ONLY"

SECTION X.

PHYSICAL DATA

Boiling point: >212°F

Specific Gravity, (water + 1.0): 1.015

% Volatile/ volume: 90%

Solubility: Complete

Description/odor: Colorless, slightly hazy liquid with mint odor.

Vapor Density: (Air = 1): ND

pH, Neat: 9.59

Vapor Pressure: ND

Evaporation Rate: slower than butyl acetate

SECTION XI.

TOXICOLOGICAL INFORMATION

♦ Effects of acute exposure to product: Liquid and vapor irritating to eyes, skin and respiratory tract.

♦ Effects of chronic exposure to product: Prolonged skin contact may result in defatting of the skin, which can lead to dermatitis. High vapor concentrations may result in CNS depression.

SECTION XII.

ECOLOGICAL INFORMATION

NOT DETERMINED.....

SECTION XIII.

ACCIDENTAL RELEASE MEASURES/ DISPOSAL INFORMATION

Large spills cannot occur because of packaging. Material should be soaked onto absorbent and shoveled into metal waste containers. Dispose of contaminated absorbent material in accordance to local, state and federal regulations. Do not release to open, public waters.

SECTION XIV.

TRANSPORT INFORMATION

Hazardous according to Table 49 CFR 172.101: **COMBUSTIBLE LIQUID, N.O.S. (1-Methoxy-2-Propanol), COMBUSTIBLE LIQUID, UN 1993, III.**

Combustible Liquid: This material is not regulated under 49 CFR if in a container of 119 gallon capacity or less.

SECTION XV.

REGULATORY INFORMATION

SARA TITLE III REPORTING REQUIREMENTS

SECTION 302: Not listed

SECTION 311: Fire hazard

SECTION 312: Fire hazard

SECTION 313: Not listed

CERCLA: Not Reportable.

RCRA: A waste containing this product may have the RCRA hazardous waste no. D001 (Ignitable) (40 CFR 261.22).

SECTION XVI.

ADDITIONAL INFORMATION

NONE.....

The information contained herein is based on data available to us and is believed to be correct. We make no warranty, however, expressed or implied regarding the accuracy of these data or the results obtained from the use thereof.

Regulatory Standards: DOT TITLE 49, Code of Federal Regulations 172.101: Parts 100 to 177, Revised 10/1/92.

SUPER FUND AMENDMENTS REAUTHORIZATION ACT OF 1986, TITLE III TOXIC SUBSTANCE CONTROL ACT LIST (TSCA)-INGREDIENTS LISTED. REGISTRY OF TOXIC EFFECTS OF CHEMICAL SUBSTANCES NATIONAL TOXICOLOGICAL PROGRAM (NTP) REPORT OF CARCINOGENS INTERNATIONAL AGENCY FOR RESEARCH ON CANCER (IARC) MONOGRAPHS, OCCUPATIONAL SAFETY & HEALTH REGULATIONS. CODE OF FED. REGS. FOOD & DRUG, 21 PARTS 170 to 199, Revised 4/1/91, 173.310.